

# Compare Xtreme Hard Concrete Densifier to Other Concrete Densifiers

Xtreme Hard Concrete Densifier is superior to traditional concrete densifiers in every way possible. Check out the chart below to see how Xtreme Hard Concrete Densifier compares to nine other concrete densifiers. Xtreme Hard Concrete Densifier provides superior performance while saving you valuable time and money.

	<b>Xtreme Hard</b>	<b>Convergence Pentra-Sil</b>	<b>Euclid Chemical Euco Diamond Hard</b>	<b>W. R. Meadows Liqui-Hard</b>	<b>Applied Concrete Technology Procreate Densifier</b>
<b>Made with Colloidal Silica</b>	<b>Yes</b>	<b>No</b> (nano lithium silicate)	<b>No</b> (silicate & silicate polymers)	<b>No</b> (sodium silicate)	<b>Yes</b>
<b>Fast &amp; easy Spray on only application</b>	<b>Yes</b>	<b>No</b> (Sprayed on, but curing agent must be applied afterwards)	<b>No</b>	<b>No</b>	<b>Yes</b>
<b>Must be broom worked into concrete</b>	<b>No</b>	<b>No</b>	<b>Yes</b>	<b>Yes</b>	<b>No</b>
<b>Set time before polishing</b>	<b>1 hr</b>	<b>N/A</b> Polishing not recommended	<b>24 hours</b>	<b>28 days</b>	<b>1 hr</b>
<b>Square ft. coverage per working gallon</b>	<b>500 to 800</b>	<b>250 - 550</b>	<b>200 - 250</b>	<b>300</b>	<b>200</b>
<b>Whiting can be a problem</b>	<b>No</b>	<b>No</b>	<b>Yes</b>	<b>Yes</b>	<b>Yes</b>
<b>Shipped in concentrate (saves money)</b>	<b>Yes</b> Reduces shipping weight by 80%	<b>No</b>	<b>No</b>	<b>No</b>	<b>No</b>
<b>Qualifies for LEED Certification Points</b>	<b>Yes</b>	<b>No</b>	<b>No</b>	<b>No</b>	<b>Yes</b>
<b>Waste must be removed</b>	<b>No</b>	<b>No</b>	<b>Yes</b>	<b>Yes</b>	<b>No</b>

	<b>Xtreme Hard</b>	Curecrete - Ashford Formula	RetroPlate System	Prosoco - Consolideck LS	Scofield Formula One Lithium Densifier MP	L & M - SealHard
Made with Colloidal Silica	<b>Yes</b>	<b>No</b> (modified sodium silicate)	<b>No</b> (modified sodium silicate)	<b>No</b> (lithium silicate)	<b>No</b> (lithium silicate)	<b>No</b> (alkali silicate)
Fast & easy Spray on only application	<b>Yes</b>	<b>No</b>	<b>No</b>	<b>Yes</b>	<b>No</b>	<b>No</b>
Must be broom worked into concrete	<b>No</b>	<b>Yes</b>	<b>Yes</b>	<b>No</b>	<b>Yes</b>	<b>Yes</b>
Set time before polishing	<b>1 hr</b>	<b>24 Hours</b>	RetroPlate does not provide this information in their publicly available literature	<b>1 hour</b>	Overnight	L & M does not provide this information in their publicly available literature
Square ft. coverage per working gallon	<b>500 to 800</b>	<b>200</b>	<b>200</b>	<b>500 - 800</b>	<b>200 - 400</b>	<b>200</b>
Whiting can be a problem	<b>No</b>	<b>Yes</b>	<b>Yes</b>	<b>Yes</b>	<b>Yes</b>	<b>Yes</b>
Shipped in concentrate (saves money)	<b>Yes</b> Reduces shipping weight by 80%	<b>No</b>	<b>No</b>	<b>No</b>	<b>No</b>	<b>No</b>
Qualifies for LEED Certification Points	<b>Yes</b>	<b>No</b>	<b>Yes</b>	<b>Yes</b>	<b>No</b>	<b>No</b>
Waste must be removed	<b>No</b>	<b>Yes</b>	<b>Yes</b>	<b>Yes</b>	<b>Yes</b>	<b>Yes</b>